

Supplied By: *StaFast Building Products*
7095 Americana Parkway
Reynoldsburg, Ohio 43068
1-800-225-4714

Trade Name: *RoofKit Contact Adhesive*

Material Safety Data Sheet



Revision Number: 001.0

Issue date: 04/08/2010

1. PRODUCT AND COMPANY IDENTIFICATION

Product name: RK CONTACT ADH ADV FORMULA
Product type: Adhesive

IDH number: 1438484

Region: United States

Company address:
Henkel Corporation
One Henkel Way
Rocky Hill, Connecticut 06067

Contact information:
Telephone: 860.571.5100
Emergency phone: 860-571-5100
Internet: www.henkelna.com

Transport: CHEMTREC 800-424-9300 For Chemical Emer. 24 hrs

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

Physical state: Liquid
Color: Natural color
Odor: Solvent

HMIS:

HEALTH: *2
FLAMMABILITY: 3
PHYSICAL HAZARD: 0
Personal Protection: See MSDS Section 8

DANGER: FLAMMABLE LIQUID AND VAPOR.
CAUSES EYE, SKIN AND RESPIRATORY TRACT IRRITATION.
MAY CAUSE CENTRAL NERVOUS SYSTEM EFFECTS.
MAY CAUSE ALLERGIC SKIN AND RESPIRATORY REACTION.

Relevant routes of exposure: Skin, Inhalation, Eyes

Potential Health Effects

Inhalation: May cause central nervous system effects with nausea, dizziness and headache. May cause irritation to nose and throat. May cause allergic respiratory reaction. Product contains toluene which is harmful or fatal if inhaled or absorbed through the skin, may cause permanent nervous system damage upon repeated exposure, and has been shown to be a human reproductive hazard.

Skin contact: May cause severe irritation due to defatting of skin. May cause allergic skin reaction.

Eye contact: Liquid or vapor can cause moderate to severe irritation. Prolonged eye contact may cause severe eye damage.

Ingestion: Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea. Aspirated material can enter the lungs and result in pneumonitis.

Existing conditions aggravated by exposure: Pre-existing skin, respiratory, central nervous system, liver and kidney conditions may be susceptible.

This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

See Section 11 for additional toxicological information.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous components	CAS NUMBER	%
Toluene	108-88-3	30 - 60
Formaldehyde phenolic resin	Proprietary	5 - 10
Naphtha (petroleum), hydrotreated heavy, <0.1% Benzene	64742-48-9	1 - 5
Naphtha, ligroine	Proprietary	1 - 5
Solvent naphtha (petroleum), light aliphatic	Proprietary	1 - 5

IDH number: 1438484

Product name: RK CONTACT ADH ADV FORMULA

4. FIRST AID MEASURES

Inhalation:	Move to fresh air. If not breathing, give artificial respiration. Get immediate medical attention.
Skin contact:	Immediately wash skin thoroughly with soap and water. Remove contaminated clothing and footwear. Get immediate medical attention.
Eye contact:	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get immediate medical attention.
Ingestion:	DO NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Get immediate medical attention.

5. FIRE FIGHTING MEASURES

Flash point:	7.20 °C (44.96 °F)
Autoignition temperature:	Not determined
Flammable/Explosive limits - lower:	Not determined
Flammable/Explosive limits - upper:	Not determined
Extinguishing media:	Foam, dry chemical or carbon dioxide.
Special firefighting procedures:	Firefighters should wear self-contained breathing apparatus. Water may be ineffective, but may be used to cool exposed containers to prevent pressure build-up and possible auto-ignition or explosion when exposed to extreme heat. If water is used, fog nozzles are preferable.
Unusual fire or explosion hazards:	Overexposure to decomposition products may cause a health hazard.
Hazardous combustion products:	Smoke. Oxides of carbon.

6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions:	Prevent further leakage or spillage if safe to do so. Do not allow material to contaminate ground water system. Do not allow product to enter sewer or waterways.
Clean-up methods:	Keep unnecessary personnel away. Ensure adequate ventilation. Wear appropriate protective equipment and clothing during clean-up. Dispose of contaminated material as waste according to item 13.

7. HANDLING AND STORAGE

Handling:	Remove all sources of ignition. Prevent contact with eyes, skin and clothing. Do not breathe vapor and mist. Wash thoroughly after handling. Make sure containers are properly grounded before use or transfer of material.
Storage:	For safe storage, store at or below 46 °C (114.8 °F)

For information on product shelf life contact Henkel Customer Service at (800) 243-4874.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous components	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Toluene	20 ppm TWA	200 ppm TWA 300 ppm Ceiling ¹ 500 ppm MAX. CONC 10 minutes	None	None
Formaldehyde phenolic resin	None	None	None	None
Naphtha (petroleum), hydrotreated heavy, <0.1% Benzene	None	None	None	196 ppm TWA
Naphtha, ligroine	None	None	None	None
Solvent naphtha (petroleum), light aliphatic	None	None	None	None

Engineering controls:	Work should be done in an adequately ventilated area (i.e., ventilation sufficient to maintain concentrations below one half of the PEL and other relevant standards). Local exhaust ventilation is recommended when general ventilation is not sufficient to control airborne contamination.
Respiratory protection:	Use NIOSH approved respirator if there is potential to exceed exposure limit(s). Observe OSHA regulations for respiratory use (29 CFR 1910.134).
Eye/face protection:	Safety goggles or safety glasses with side shields. Full face protection should be used if the potential for splashing or spraying of product exists.
Skin protection:	Use impermeable gloves and protective clothing as necessary to prevent skin contact. Wear suitable protective clothing.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:	Liquid
Color:	Natural color
Odor:	Solvent
Odor threshold:	Not available
pH:	Not determined
Vapor pressure:	Not determined
Boiling point/range:	> 110 °C (> 230°F)
Melting point/ range:	Not determined
Specific gravity:	0.70
Vapor density:	Not determined
Flash point:	7.20 °C (44.96 °F)
Flammable/Explosive limits - lower:	Not determined
Flammable/Explosive limits - upper:	Not determined
Autoignition temperature:	Not determined
Evaporation rate:	Slower than diethyl ether.
Solubility in water:	Insoluble
Partition coefficient (n-octanol/water):	Not determined
VOC content:	670 g/l

10. STABILITY AND REACTIVITY

Stability:	Stable at normal conditions.
Hazardous reactions:	Will not occur.
Hazardous decomposition products:	Burning, including when heated by welding or cutting, will produce smoke, carbon monoxide and carbon dioxide.
Incompatible materials:	Strong acids and strong bases. Oxidizing agents.
Conditions to avoid:	Avoid excessive heat (>46°C (>115°F)) and sources of ignition.

11. TOXICOLOGICAL INFORMATION

Hazardous components	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Toluene	No	No	No
Formaldehyde phenolic resin	No	No	No
Naphtha (petroleum), hydrotreated heavy, <0.1% Benzene	No	No	No
Naphtha, ligroine	No	No	No
Solvent naphtha (petroleum), light aliphatic	No	No	No

Hazardous components	Health Effects/Target Organs
Toluene	Behavioral, Cardiac, Central nervous system, Developmental, Ear, Irritant
Formaldehyde phenolic resin	Irritant, Allergen
Naphtha (petroleum), hydrotreated heavy, <0.1% Benzene	Irritant
Naphtha, ligroine	Central nervous system, Irritant
Solvent naphtha (petroleum), light aliphatic	Irritant

12. ECOLOGICAL INFORMATION

Ecological information: Not available

13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal: Legal disposition of wastes is the responsibility of the owner/generator of the waste. Applicable federal, state and/or local regulations must be followed during treatment, storage, or disposal of waste containing this product.

Hazardous waste number: D001: Ignitable.

14. TRANSPORT INFORMATION**U.S. Department of Transportation Ground (49 CFR)**

Proper shipping name: Adhesives
Hazard class or division: 3
Identification number: UN 1133
Packing group: II
DOT Reportable quantity: Toluene

International Air Transportation (ICAO/IATA)

Proper shipping name: Adhesives
Hazard class or division: 3
Identification number: UN 1133
Packing group: II

Water Transportation (IMO/IMDG)

Proper shipping name: ADHESIVES
Hazard class or division: 3
Identification number: UN 1133
Packing group: II

15. REGULATORY INFORMATION**United States Regulatory Information**

TSCA 8 (b) Inventory Status: All components are listed or are exempt from listing on the Toxic Substances Control Act Inventory.
TSCA 12(b) Export Notification: None above reporting de minimus

CERCLA/SARA Section 302 EHS:	None above reporting de minimus
CERCLA/SARA Section 311/312:	Immediate Health, Delayed Health, Fire
CERCLA/SARA 313:	This product contains the following toxic chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 (40 CFR 372). Toluene (CAS# 108-88-3).
CERCLA Reportable quantity:	Toluene (CAS# 108-88-3) 1,000 lbs. (454 kg)
California Proposition 65:	This product contains a chemical known in the State of California to cause cancer. This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

Canada Regulatory Information

CEPA DSL/NDL Status:	All components are listed on or are exempt from listing on the Canadian Domestic Substances List.
WHMIS hazard class:	B.2, D.2.A, D.2.B

16. OTHER INFORMATION

This material safety data sheet contains changes from the previous version in sections: New Material Safety Data Sheet format.

Prepared by: Jennifer Altman, Sr. Regulatory Affairs Specialist

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation does not assume responsibility for any results obtained by persons over whose methods Henkel Corporation has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any of Henkel Corporation's products. In light of the foregoing, Henkel Corporation specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel Corporation's products. Henkel Corporation further disclaims any liability for consequential or incidental damages of any kind, including lost profits.