

Supplied By: *StaFast Building Products*  
 7095 Americana Parkway  
 Reynoldsburg, Ohio 43068  
 1-800-225-4714  
 Trade Name: *Roof Kit Seam Primer*

Page: 1

Revision Date: 11/12/2009

Print Date: 1/21/2010

MSDS Number: R0272451

Version: 1.10

ROOF KIT SEAM 120363

## 1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

Ashland	Regulatory Information Number	1-800-325-3751
P.O. Box 2219	Telephone	614-790-3333
Columbus, OH 43216	Emergency telephone	1-800-ASHLAND (1-800-274-5263)
Product name	ROOF KIT SEAM	For Chemical Emergency:
Product code	120363	Call CHEMTREC AT 800-424-9300
Product Use Description	Adhesives	

## 2. HAZARDS IDENTIFICATION

### Emergency Overview

Appearance: liquid,, colourless

**DANGER! EXTREMELY FLAMMABLE LIQUID AND VAPOR. VAPOR MAY CAUSE FLASH FIRE. MAY AFFECT THE CENTRAL NERVOUS SYSTEM CAUSING DIZZINESS, HEADACHE OR NAUSEA. MAY BE HARMFUL IF INHALED. MAY CAUSE EYE, SKIN AND RESPIRATORY TRACT IRRITATION. PROLONGED OR REPEATED CONTACT MAY DRY SKIN, CAUSE IRRITATION AND BURNS.**

### Potential Health Effects

#### **Exposure routes**

Inhalation, Skin absorption, Skin contact, Eye Contact, Ingestion

#### **Eye contact**

Can cause eye irritation. Symptoms include stinging, tearing, redness, and swelling of eyes. Additional symptoms of eye exposure may include: blurred vision

#### **Skin contact**

Can cause skin irritation. Prolonged or repeated contact may dry the skin. Symptoms may include redness, burning, and drying and cracking of skin, burns and other skin damage. Additional symptoms of skin contact may include: Blistering Passage of this material into the body through the skin is possible, but it is unlikely that this would result in harmful effects during safe handling and use.

**ASHLAND**  
**SAFETY DATA SHEET**

Page: 2

Revision Date: 11/12/2009

Print Date: 1/21/2010

MSDS Number: R0272451

Version: 1.10

ROOF KIT SEAM 120363

**Ingestion**

Swallowing small amounts of this material during normal handling is not likely to cause harmful effects. Swallowing large amounts may be harmful. This material can get into the lungs during swallowing or vomiting. This results in lung inflammation and other lung injury.

**Inhalation**

Breathing of vapor or mist is possible. Breathing small amounts of this material during normal handling is not likely to cause harmful effects. Breathing large amounts may be harmful. Symptoms are not expected at air concentrations below the recommended exposure limits, if applicable (see Section 8.).

**Aggravated Medical Condition**

Preexisting disorders of the following organs (or organ systems) may be aggravated by exposure to this material: respiratory tract, skin, lung (for example, asthma-like conditions), liver, kidney, central nervous system, heart, male reproductive system, auditory system, Individuals with preexisting heart disorders maybe more susceptible to arrhythmias (irregular heartbeats) if exposed to high concentrations of this material. Preexisting disorders of the following organs (or organ systems) may be aggravated by exposure to this material: Upper respiratory tract, Skin, lung (for example, asthma-like conditions), kidney, Central nervous system, auditory system, Individuals with preexisting heart disorders maybe more susceptible to arrhythmias (irregular heartbeats) if exposed to high concentrations of this material., Kidney, male reproductive system, Liver

**Symptoms**

Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through the skin may include: metallic taste, stomach or intestinal upset (nausea, vomiting, diarrhea), irritation (nose, throat, airways), central nervous system excitation (giddiness, liveliness, light-headed feeling) followed by central nervous system depression (dizziness, drowsiness, weakness, fatigue, nausea, headache, unconsciousness) and other central nervous system effects, temporary changes in mood and behavior, Weakness, Lack of coordination, confusion, irregular heartbeat, coma, runny nose, redness of the skin, effects on memory, respiratory depression (slowing of the breathing rate), Shortness of breath, narcosis (dazed or sluggish feeling), central nervous system depression (dizziness, drowsiness, weakness, fatigue, nausea, headache, unconsciousness), discomfort in the chest, anesthesia, loss of appetite

**Target Organs**

Exposure to this material (or a component) has been found to cause kidney damage in male rats. The mechanism by which this toxicity occurs is specific to the male rat and the kidney effects are not expected to occur in humans., Prolonged intentional

**ASHLAND**  
**SAFETY DATA SHEET**

Page: 3

Revision Date: 11/12/2009

Print Date: 1/21/2010

MSDS Number: R0272451

Version: 1.10

ROOF KIT SEAM 120363

toluene abuse may lead to damage to many organ systems having effects on: central and peripheral nervous systems, vision, hearing, liver, kidneys, heart and blood. Such abuse has been associated with brain damage characterized by disturbances in gait, personality changes and loss of memory. Comparable central nervous system effects have not been shown to result from occupational exposure to toluene., Prolonged intentional toluene abuse may lead to hearing loss progressing to deafness. In addition, while noise is known to cause hearing loss in humans, it has been suggested that workers exposed to organic solvents, including toluene, along with noise may suffer greater hearing loss than would be expected from exposure to noise alone., Overexposure to this material (or its components) has been suggested as a cause of the following effects in laboratory animals:., respiratory tract damage (nose, throat, and airways), kidney damage, liver damage, effects on hearing, testis damage, lung damage, central nervous system damage, Overexposure to this material (or its components) has been suggested as a cause of the following effects in humans:., cardiac abnormalities, cardiac sensitization, visual impairment, kidney damage, central nervous system effects, Prolonged and repeated exposure to n-hexane may cause peripheral neuropathy by damaging peripheral nerve tissue (that of the arms and legs) and result in muscular weakness and loss of sensation., Prolonged and repeated inhalation of high levels of mixed isomers of hexane resulted in kidney damage in male rats. The effects observed are the same as those seen in male rats exposed to other hydrocarbons. The mechanism by which these chemicals cause the characteristic kidney toxicity is unique to the male rat and the kidney effects are not expected to occur in man.Prolonged intentional toluene abuse may lead to damage to many organ systems having effects on: central and peripheral nervous systems, vision, hearing, liver, kidneys, heart and blood. Such abuse has been associated with brain damage characterized by disturbances in gait, personality changes and loss of memory. Comparable central nervous system effects have not been shown to result from occupational exposure to toluene., Prolonged intentional toluene abuse may lead to hearing loss progressing to deafness. In addition, while noise is known to cause hearing loss in humans, it has been suggested that workers exposed to organic solvents, including toluene, along with noise may suffer greater hearing loss than would be expected from exposure to noise alone., Overexposure to this material (or its components) has been suggested as a cause of the following effects in laboratory animals:., mild, reversible liver effects, mild, reversible kidney effects, respiratory tract damage (nose, throat, and airways), effects on hearing, central nervous system damage, Overexposure to this material (or its components) has been suggested as a cause of the following effects in humans:., kidney damage, cardiac sensitization, kidney damage, Exposure to this material (or a component) has been found to cause kidney damage in male rats. The mechanism by which this toxicity occurs is specific to the male rat and the kidney effects are not expected to occur in humans., Prolonged and repeated exposure to n-hexane may cause peripheral neuropathy by damaging peripheral nerve tissue (that of the arms and legs) and result in muscular weakness and loss of sensation., nasal damage, nervous system damage, testis damage, lung damage, visual impairment, central nervous system effects,

# ASHLAND

## SAFETY DATA SHEET

Page: 4

Revision Date: 11/12/2009

Print Date: 1/21/2010

MSDS Number: R0272451

Version: 1.10

ROOF KIT SEAM 120363

testis damage, liver damage, central nervous system effects, liver abnormalities, kidney abnormalities, effects on hearing

### Carcinogenicity

Ethylbenzene has been shown to cause cancer in laboratory animals. The relevance of this finding to humans is uncertain. The International Agency for Research on Cancer (IARC) has classified ethylbenzene as a possible human carcinogen. In testing of C-6 isomers for carcinogenicity by inhalation, there was a treatment-related increase in liver tumors (adenomas and carcinomas) in female mice at the highest dose only (9,000 ppm). There was no increase in tumor incidence in male mice or in rats of either sex at any dose level. This material is not listed as a carcinogen by the International Agency for Research on Cancer (IARC), the National Toxicology Program (NTP), or the Occupational Safety and Health Administration (OSHA). Based on the available information, this material cannot be classified with regard to carcinogenicity. Ethylbenzene has been shown to cause cancer in laboratory animals. The relevance of this finding to humans is uncertain. The International Agency for Research on Cancer (IARC) has classified ethylbenzene as a possible human carcinogen. There is no information available. The chance of this material causing cancer is unknown.

### Reproductive hazard

This material (or a component) has been shown to cause birth defects in laboratory animal studies. The relevance of these findings to humans is uncertain., Toluene may be harmful to the human fetus based on positive test results with laboratory animals. Case studies show that prolonged intentional abuse of toluene during pregnancy can cause birth defects in humans. Toluene may be harmful to the human fetus based on positive test results with laboratory animals. Case studies show that prolonged intentional abuse of toluene during pregnancy can cause birth defects in humans., This material (or a component) may be harmful to the human fetus based on positive test results with laboratory animals., This material (or a component) has been shown to cause harm to the fetus in laboratory animal studies. Harm to the fetus occurs only at exposure levels that harm the pregnant animal. The relevance of these findings to humans is uncertain., There are no data available for assessing risk to the fetus from maternal exposure to this material.

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

Components	CAS-No.	Concentration
TOLUENE	108-88-3	>=50-<60%
XYLENE	1330-20-7	>=10-<15%
SOLVENT NAPHTHA	64742-89-8	>=5-<10%

# ASHLAND

## SAFETY DATA SHEET

ROOF KIT SEAM 120363

Page: 5  
 Revision Date: 11/12/2009  
 Print Date: 1/21/2010  
 MSDS Number: R0272451  
 Version: 1.10

Components	CAS-No.	Concentration
(PETROLEUM), LIGHT ALIPHATIC		
N-HEXANE	110-54-3	>=5-<10%
ETHYL BENZENE	100-41-4	>=1.5-<5%
CYCLOHEXANE	110-82-7	>=1.5-<5%
n-HEPTANE	142-82-5	>=1-<1.5%
POLYISOCYANATE	TRADE SECRET	>=1-<1.5%

#### 4. FIRST AID MEASURES

##### Eyes

If symptoms develop, immediately move individual away from exposure and into fresh air. Flush eyes gently with water for at least 15 minutes while holding eyelids apart; seek immediate medical attention.

##### Skin

Remove contaminated clothing. Flush exposed area with large amounts of water. If skin is damaged, seek immediate medical attention. If skin is not damaged and symptoms persist, seek medical attention. Launder clothing before reuse.

##### Ingestion

Seek medical attention. If individual is drowsy or unconscious, do not give anything by mouth; place individual on the left side with the head down. Contact a physician, medical facility, or poison control center for advice about whether to induce vomiting. If possible, do not leave individual unattended.

##### Inhalation

If symptoms develop, immediately move individual away from exposure and into fresh air. Seek immediate medical attention; keep person warm and quiet. If person is not breathing, begin artificial respiration. If breathing is difficult, administer oxygen.

##### Notes to physician

**Hazards:** Inhalation of high concentrations of this material, as could occur in enclosed spaces or during deliberate abuse, may be associated with cardiac arrhythmias. Sympathomimetic drugs may initiate cardiac arrhythmias in persons exposed to this material. This material is an aspiration hazard. Potential danger from aspiration must be weighed against possible oral toxicity (See Section 2 - Swallowing) when deciding whether to induce vomiting.

**Treatment:** No information available.

**ASHLAND**  
**SAFETY DATA SHEET**

ROOF KIT SEAM 120363

Page: 6  
Revision Date: 11/12/2009  
Print Date: 1/21/2010  
MSDS Number: R0272451  
Version: 1.10**5. FIRE-FIGHTING MEASURES****Suitable extinguishing media**ABC powder, Water mist, Carbon dioxide (CO<sub>2</sub>), Dry chemical**Hazardous combustion products**carbon dioxide and carbon monoxide, halogenated hydrocarbons, nitrogen oxides (NO<sub>x</sub>), various hydrocarbons, Aldehydes**Precautions for fire-fighting**

Material is volatile and readily gives off vapors which may travel along the ground or be moved by ventilation and ignited by pilot lights, flames, sparks, heaters, smoking, electric motors, static discharge or other ignition sources at locations near the material handling point. Never use welding or cutting torch on or near drum (even empty) because product (even just residue) can ignite explosively. Wear full firefighting turn-out gear (full Bunker gear), and respiratory protection (SCBA).

**6. ACCIDENTAL RELEASE MEASURES****Personal precautions**

For personal protection see section 8. Eliminate all ignition sources (flares, flames including pilot lights, electrical sparks). Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed. Stop spill at source. Prevent from entering drains, sewers, streams or other bodies of water. Prevent from spreading. If runoff occurs, notify authorities as required. Pump or vacuum transfer spilled product to clean containers for recovery. Absorb unrecoverable product. Transfer contaminated absorbent, soil and other materials to containers for disposal.

**Environmental precautions**

No data

**Methods for cleaning up**

Absorb liquid on vermiculite, floor absorbent, or other absorbent material and transfer to hood.

**7. HANDLING AND STORAGE****Handling**

Containers of this material may be hazardous when emptied. Since emptied containers retain product residues (vapor, liquid, and/or solid), all hazard precautions

# ASHLAND

## SAFETY DATA SHEET

Page: 7

Revision Date: 11/12/2009

Print Date: 1/21/2010

MSDS Number: R0272451

Version: 1.10

ROOF KIT SEAM 120363

given in the data sheet must be observed. Static ignition hazard can result from handling and use. Electrically bond and ground all containers, personnel and equipment before transfer or use of material. Special precautions may be necessary to dissipate static electricity for non-conductive containers. Use proper bonding and grounding during product transfer as described in National Fire Protection Association document NFPA 77.

### Storage

Store in a cool, dry, ventilated area, away from incompatible substances. Keep containers closed when not in use. Do not store near extreme heat, open flame, or sources of ignition.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Exposure Guidelines

<b>TOLUENE</b>		<b>108-88-3</b>
ACGIH	time weighted average	20 ppm
NIOSH	Recommended exposure limit (REL):	100 ppm
NIOSH	Recommended exposure limit (REL):	375 mg/m3
NIOSH	Short term exposure limit	150 ppm
NIOSH	Short term exposure limit	560 mg/m3
OSHA Z2	time weighted average	200 ppm
OSHA Z2	Ceiling Limit Value:	300 ppm
OSHA Z2	Maximum concentration:	500 ppm
<b>XYLENE</b>		<b>1330-20-7</b>
ACGIH	time weighted average	100 ppm
ACGIH	Short term exposure limit	150 ppm
OSHA Z1	Permissible exposure limit	100 ppm
OSHA Z1	Permissible exposure limit	435 mg/m3
NIOSH	Recommended exposure limit (REL):	100 ppm
NIOSH	Recommended exposure limit (REL):	435 mg/m3
NIOSH	Short term exposure limit	150 ppm
NIOSH	Short term exposure limit	655 mg/m3
<b>N-HEXANE</b>		<b>110-54-3</b>
ACGIH	time weighted average	50 ppm
NIOSH	Recommended exposure limit (REL):	50 ppm
NIOSH	Recommended exposure limit (REL):	180 mg/m3

# ASHLAND

## SAFETY DATA SHEET

Page: 8

Revision Date: 11/12/2009

Print Date: 1/21/2010

MSDS Number: R0272451

Version: 1.10

ROOF KIT SEAM 120363

OSHA Z1	Permissible exposure limit	500 ppm
OSHA Z1	Permissible exposure limit	1,800 mg/m3

### ETHYL BENZENE 100-41-4

ACGIH	time weighted average	100 ppm
ACGIH	Short term exposure limit	125 ppm
NIOSH	Recommended exposure limit	100 ppm
	(REL):	
NIOSH	Recommended exposure limit	435 mg/m3
	(REL):	
NIOSH	Short term exposure limit	125 ppm
NIOSH	Short term exposure limit	545 mg/m3
OSHA Z1	Permissible exposure limit	100 ppm
OSHA Z1	Permissible exposure limit	435 mg/m3

### CYCLOHEXANE 110-82-7

ACGIH	time weighted average	100 ppm
OSHA Z1	Permissible exposure limit	300 ppm
OSHA Z1	Permissible exposure limit	1,050 mg/m3
NIOSH	Recommended exposure limit	300 ppm
	(REL):	
NIOSH	Recommended exposure limit	1,050 mg/m3
	(REL):	

### n-HEPTANE 142-82-5

ACGIH	time weighted average	400 ppm
ACGIH	Short term exposure limit	500 ppm
NIOSH	Recommended exposure limit	85 ppm
	(REL):	
NIOSH	Recommended exposure limit	350 mg/m3
	(REL):	
NIOSH	Ceiling Limit Value and Time Period (if specified):	440 ppm
NIOSH	Ceiling Limit Value and Time Period (if specified):	1,800 mg/m3
OSHA Z1	Permissible exposure limit	500 ppm
OSHA Z1	Permissible exposure limit	2,000 mg/m3
OSHA Z1A	time weighted average	400 ppm
OSHA Z1A	time weighted average	1,600 mg/m3
OSHA Z1A	Short term exposure limit	500 ppm
OSHA Z1A	Short term exposure limit	2,000 mg/m3
US CA OEL	Time Weighted Average (TWA) Permissible Exposure Limit (PEL):	400 ppm

# ASHLAND

## SAFETY DATA SHEET

Page: 9

Revision Date: 11/12/2009

Print Date: 1/21/2010

MSDS Number: R0272451

Version: 1.10

ROOF KIT SEAM 120363

US CA OEL	Time Weighted Average (TWA) Permissible Exposure Limit (PEL):	1,600 mg/m <sup>3</sup>
US CA OEL	Short term exposure limit	500 ppm
US CA OEL	Short term exposure limit	2,000 mg/m <sup>3</sup>
ACGIH	time weighted average	400 ppm
ACGIH	Short term exposure limit	500 ppm

### General advice

These recommendations provide general guidance for handling this product. Personal protective equipment should be selected for individual applications and should consider factors which affect exposure potential, such as handling practices, chemical concentrations and ventilation. It is ultimately the responsibility of the employer to follow regulatory guidelines established by local authorities.

### Exposure controls

Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below TLV(s).

### Eye protection

Chemical splash goggles in compliance with OSHA regulations are advised; however, OSHA regulations also permit other type safety glasses. Consult your safety representative.

### Skin and body protection

Wear resistant gloves (consult your safety equipment supplier).  
To prevent repeated or prolonged skin contact, wear impervious clothing and boots.

### Respiratory protection

If workplace exposure limit(s) of product or any component is exceeded (see exposure guidelines), a NIOSH-approved air supplied respirator is advised in absence of proper environmental control. OSHA regulations also permit other NIOSH respirators (negative pressure type) under specified conditions (see your industrial hygienist). Engineering or administrative controls should be implemented to reduce exposure.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

<b>Physical state</b>	liquid
<b>Form</b>	No data
<b>Colour</b>	colourless, light yellow
<b>Odour</b>	aromatic

# ASHLAND

## SAFETY DATA SHEET

Page: 10

Revision Date: 11/12/2009

Print Date: 1/21/2010

MSDS Number: R0272451

Version: 1.10

ROOF KIT SEAM 120363

<b>Boiling point/boiling range</b>	64.00 °C / 147 °F
<b>pH</b>	No data
<b>Flash point</b>	(<)0 °F / -18 °C, Seta closed cup
<b>Evaporation rate</b>	< 1 (Ethyl Ether)
<b>Explosion limits</b>	1 %(V) 7 %(V)
<b>Vapour pressure</b>	40.90 mmHg @ 68.00 °F / 20.00 °C
<b>Vapour density</b>	(>) 1 (AIR=1)
<b>Density</b>	0.841 g/cm <sup>3</sup> @ 77.00 °F / 25.00 °C 7.01 lb/gal @ 77.00 °F / 25.00 °C
<b>Solubility</b>	insoluble in water
<b>Partition coefficient: n-octanol/water</b>	No data
<b>log Pow</b>	no data available
<b>Autoignition temperature</b>	No data

### 10. STABILITY AND REACTIVITY

#### Stability

Stable.

#### Conditions to avoid

Heat, flames and sparks., excessive heat

#### Incompatible products

Strong acids, Strong oxidizing agents, alkalis, Acids, peroxides

#### Hazardous decomposition products

carbon dioxide and carbon monoxide, Hydrocarbons, Aldehydes, organic compounds

#### Hazardous reactions

Product will not undergo hazardous polymerization.

#### Thermal decomposition

No data

### 11. TOXICOLOGICAL INFORMATION

#### Acute oral toxicity

TOLUENE

LD 50 Rat: 2,600 - 7,500 mg/kg

# ASHLAND

## SAFETY DATA SHEET

Page: 11

Revision Date: 11/12/2009

Print Date: 1/21/2010

MSDS Number: R0272451

Version: 1.10

ROOF KIT SEAM 120363

XYLENE	LD 50 Rat: 4,300 mg/kg
SOLVENT NAPHTHA (PETROLEUM), LIGHT ALIPHATIC	LD 50 Rat: > 8,000 mg/kg
N-HEXANE	LD 50 Rat: 25 g/kg
ETHYL BENZENE	LD 50 Rat: 3,500 mg/kg
CYCLOHEXANE	LD 50 Rat: 29,820 mg/kg LD 50 Mouse: 1,300 mg/kg
n-HEPTANE	LD 50 Rat: > 15,000 mg/kg
POLYISOCYANATE	no data available

### Acute inhalation toxicity

TOLUENE	LC 50 Rat: 8000 ppm, 4 h
XYLENE	no data available
SOLVENT NAPHTHA (PETROLEUM), LIGHT ALIPHATIC	LC 50 Rat: 3400 ppm, 4 h
N-HEXANE	LC 50 Rat: 48000 ppm, 4 h
ETHYL BENZENE	LC Lo Rat: 4000 ppm, 4 h
CYCLOHEXANE	LC 50 Rat: > 4044 ppm,
n-HEPTANE	LC 50 Rat: 103 g/m3 , 4 h LC 50 Rat: 103 g/m3 , 4 h LD 50 Mouse: 75 g/m3 , 2 h
POLYISOCYANATE	no data available

### Acute dermal toxicity

TOLUENE	LD 50 Rabbit: 12,124 mg/kg
XYLENE	LD 50 Rabbit: > 2,000 mg/kg
SOLVENT NAPHTHA (PETROLEUM), LIGHT ALIPHATIC	LD 50 Rat: > 4,000 mg/kg
N-HEXANE	LD 50 Rabbit: > 1.3 g/kg
ETHYL BENZENE	LD 50 Rabbit: 17,800 mg/kg
CYCLOHEXANE	LD 50 Rabbit: > 2.0 g/kg

# ASHLAND

## SAFETY DATA SHEET

Page: 12

Revision Date: 11/12/2009

Print Date: 1/21/2010

MSDS Number: R0272451

Version: 1.10

ROOF KIT SEAM 120363

n-HEPTANE	LD 50 Rabbit: > 2,001 mg/kg
POLYISOCYANATE	no data available

### 12. ECOLOGICAL INFORMATION

#### Aquatic toxicity

##### Acute and Prolonged Toxicity to Fish

No data

##### Acute Toxicity to Aquatic Invertebrates

No data

#### Environmental fate and pathways

No data

### 13. DISPOSAL CONSIDERATIONS

#### Waste disposal methods

Destroy by liquid incineration in accordance with applicable regulations. For assistance with your waste management needs - including disposal, recycling and waste stream reduction, contact Ashland Distribution's Environmental Services Group at 800-637-7922.

### 14. TRANSPORT INFORMATION

#### IMDG:

UN1133, ADHESIVES 3, II

#### IATA\_P:

UN1133, Adhesives 3, II

#### IATA\_C:

UN1133, Adhesives 3, II

#### CFR\_ROAD:

UN1133, Adhesives 3, II

#### CFR\_RAIL:

UN1133, Adhesives 3, II

#### CFR\_INWTR:

UN1133, Adhesives 3, II

#### IMDG\_ROAD:

UN1133, ADHESIVES 3, II

# ASHLAND

## SAFETY DATA SHEET

ROOF KIT SEAM 120363

Page: 13

Revision Date: 11/12/2009

Print Date: 1/21/2010

MSDS Number: R0272451

Version: 1.10

**IMDG\_RAIL:**

UN1133, ADHESIVES 3, II

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

### 15. REGULATORY INFORMATION

**California Prop. 65**

WARNING! This product contains a chemical known in the State of California to cause cancer.

ETHYL BENZENE

BENZENE

WARNING! This product contains a chemical known in the State of California to cause birth defects or other reproductive harm.

TOLUENE

BENZENE

**SARA Hazard Classification**

Fire Hazard
Acute Health Hazard
Chronic Health Hazard

**SARA 313 Component(s)**

TOLUENE	108-88-3	56.42%
XYLENE	1330-20-7	14.62%
N-HEXANE	110-54-3	7.60%
ETHYL BENZENE	100-41-4	4.18%
CYCLOHEXANE	110-82-7	2.01%

**New Jersey RTK Label Information**

TOLUENE	108-88-3
XYLENE	1330-20-7
SOLVENT NAPHTHA (PETROLEUM), LIGHT ALIPHATIC	64742-89-8
N-HEXANE	110-54-3
ETHYL BENZENE	100-41-4

# ASHLAND

## SAFETY DATA SHEET

Page: 14

Revision Date: 11/12/2009

Print Date: 1/21/2010

MSDS Number: R0272451

Version: 1.10

ROOF KIT SEAM 120363

CYCLOHEXANE	110-82-7
n-HEPTANE	142-82-5

### Pennsylvania RTK Label Information

TOLUENE	108-88-3
XYLENE	1330-20-7
SOLVENT NAPHTHA (PETROLEUM), LIGHT ALIPHATIC	64742-89-8
N-HEXANE	110-54-3
ETHYL BENZENE	100-41-4
CYCLOHEXANE	110-82-7
n-HEPTANE	142-82-5
BENZENE	71-43-2

### Reportable quantity - Product

US. EPA CERCLA Hazardous Substances (40 CFR 302)	683 lbs
--	---------

### Reportable quantity - Components

TOLUENE	108-88-3	1000 lbs
XYLENE	1330-20-7	100 lbs
SOLVENT NAPHTHA (PETROLEUM), LIGHT ALIPHATIC	64742-89-8	none
N-HEXANE	110-54-3	5000 lbs
ETHYL BENZENE	100-41-4	1000 lbs
CYCLOHEXANE	110-82-7	1000 lbs
n-HEPTANE	142-82-5	none
POLYISOCYANATE	TRADE SECRET	none

	Health	Flammability	Reactivity	Other
<b>HMIS</b>	2*	3	0	
<b>NFPA</b>	2	2	0	

## 16. OTHER INFORMATION

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This MSDS has been prepared by Ashland's Environmental Health and Safety Department (1-800-325-3751).