

Supplied By: *StaFast Building Products*
7095 Americana Parkway
Reynoldsburg, Ohio 43068
1-800-225-4714
Trade Name: RoofKit Waterstop Caulk

Page: 1
Revision Date: 01/20/2010
Print Date: 1/22/2010
MSDS Number: R0205917
Version: 1.11

ROOF KIT WATER STOP
165010

1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

Ashland P.O. Box 2219 Columbus, OH 43216	Regulatory Information Number Telephone Emergency telephone	1-800-325-3751 614-790-3333 1-800-ASHLAND (1-800-274-5263)
Product name	ROOF KIT WATER STOP	For Chemical Emergency: Call CHEMTREC AT 800-424-9300
Product code	165010	
Product Use Description	No data	

2. HAZARDS IDENTIFICATION

Emergency Overview

Appearance: liquid, grey

CAUTION! COMBUSTIBLE LIQUID AND VAPOR. MAY CAUSE ALLERGIC RESPIRATORY REACTION. MAY BE HARMFUL IF INHALED OR SWALLOWED.

Potential Health Effects

Exposure routes

Inhalation, Skin absorption, Skin contact, Eye Contact, Ingestion

Eye contact

May cause mild eye irritation. Symptoms include stinging, tearing, and redness.

Skin contact

May cause mild skin irritation. Symptoms may include redness and burning of skin. Passage of this material into the body through the skin is possible, but it is unlikely that this would result in harmful effects during safe handling and use.

Ingestion

Swallowing small amounts of this material during normal handling is not likely to cause harmful effects. Swallowing large amounts may be harmful. This material can get into the lungs during swallowing or vomiting. This results in lung inflammation and other lung injury.

ROOF KIT WATER STOP
165010

Inhalation

It is possible to breathe this material under certain conditions of handling and use (for example, during heating, spraying, or stirring). Breathing small amounts of this material during normal handling is not likely to cause harmful effects. Breathing large amounts may be harmful. Symptoms are not expected at air concentrations below the recommended exposure limits, if applicable (see Section 8.).

Aggravated Medical Condition

Preexisting disorders of the following organs (or organ systems) may be aggravated by exposure to this material: skin, lung (for example, asthma-like conditions), Individuals with preexisting heart disorders maybe more susceptible to arrhythmias (irregular heartbeats) if exposed to high concentrations of this material. Preexisting disorders of the following organs (or organ systems) may be aggravated by exposure to this material: Skin, lung (for example, asthma-like conditions), skin

Symptoms

Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through the skin may include: stomach or intestinal upset (nausea, vomiting, diarrhea), irritation (nose, throat, airways), Lung irritation, Blistering, central nervous system depression (dizziness, drowsiness, weakness, fatigue, nausea, headache, unconsciousness)

Target Organs

Exposure to this material (or a component) has been found to cause kidney damage in male rats. The mechanism by which this toxicity occurs is specific to the male rat and the kidney effects are not expected to occur in humans. Overexposure to this material (or its components) has been suggested as a cause of the following effects in laboratory animals: mild, reversible liver effects Exposure to this material (or a component) has been found to cause kidney damage in male rats. The mechanism by which this toxicity occurs is specific to the male rat and the kidney effects are not expected to occur in humans.

Carcinogenicity

This material is not listed as a carcinogen by the International Agency for Research on Cancer (IARC), the National Toxicology Program (NTP), or the Occupational Safety and Health Administration (OSHA). This product (or a component) is a petroleum-derived material. Similar materials and certain compounds occurring naturally in petroleum oils have been shown to cause skin cancer in laboratory animals following repeated exposure without washing or removal. Based on the available information, this material cannot be classified with regard to carcinogenicity. This material is not listed as a carcinogen by the International Agency for Research on Cancer (IARC), the National Toxicology Program (NTP), or the Occupational Safety and Health Administration (OSHA).

Reproductive hazard

ROOF KIT WATER STOP
165010

Based on the available information, risk to the fetus from maternal exposure to this material cannot be assessed. There are no data available for assessing risk to the fetus from maternal exposure to this material.

Other information

This material can form dust which may cause skin or mucous membrane irritation. Symptoms may include redness, burning, and swelling. Although they may cause respiratory tract irritation, nuisance dusts do not form scar tissue or affect the structure of air spaces in the lungs. Their effects on the tissues are potentially reversible.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous Components	CAS-No.	Concentration
MINERAL SPIRITS REGULAR	8052-41-3	>=10-<15%
POLYMER	254504001-5234	>=1.5-<5%
RESIDUAL OILS (PETROLEUM), SOLVENT-DEWAXED	64742-62-7	>=1.5-<5%
CALCIUM CARBONATE	471-34-1	>=1.5-<5%
QUATERNARY AMMONIUM MONTMORILLONITE	68953-58-2	>=1.5-<5%
KAOLIN	1332-58-7	>=1-<1.5%

4. FIRST AID MEASURES

Eyes

If symptoms develop, move individual away from exposure and into fresh air. Flush eyes gently with water while holding eyelids apart. If symptoms persist or there is any visual difficulty, seek medical attention.

Skin

Remove contaminated clothing. Flush exposed area with large amounts of water. If skin is damaged, seek immediate medical attention. If skin is not damaged and symptoms persist, seek medical attention. Launder clothing before reuse.

Ingestion

Seek medical attention. If individual is drowsy or unconscious, do not give anything by mouth; place individual on the left side with the head down. Contact a physician, medical facility, or poison

ROOF KIT WATER STOP
165010

control center for advice about whether to induce vomiting. If possible, do not leave individual unattended.

Inhalation

If symptoms develop, move individual away from exposure and into fresh air. If symptoms persist, seek medical attention. If breathing is difficult, administer oxygen. Keep person warm and quiet; seek immediate medical attention.

Notes to physician

Hazards: Inhalation of high concentrations of this material, as could occur in enclosed spaces or during deliberate abuse, may be associated with cardiac arrhythmias. Sympathomimetic drugs may initiate cardiac arrhythmias in persons exposed to this material. This material is an aspiration hazard. Potential danger from aspiration must be weighed against possible oral toxicity (See Section 2 - Swallowing) when deciding whether to induce vomiting. Ingestion of large amounts or other significant exposure to this material (or a component) may cause alkalosis. Excessive calcium intake may cause gastrointestinal symptoms, hypertension, hypercalcemia, kidney stones, and may inhibit absorption of iron, zinc, and possibly other trace elements. This material is an aspiration hazard. Potential danger from aspiration must be weighed against possible oral toxicity (See Section 2 - Swallowing) when deciding whether to induce vomiting.

Treatment: No information available.

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media

ABC powder, Water mist, Carbon dioxide (CO2), Dry chemical

Hazardous combustion products

Aldehydes, carbon dioxide and carbon monoxide, various hydrocarbons

Precautions for fire-fighting

Material is volatile and readily gives off vapors which may travel along the ground or be moved by ventilation and ignited by pilot lights, flames, sparks, heaters, smoking, electric motors, static discharge or other ignition sources at locations near the material handling point. Never use welding or cutting torch on or near drum (even empty) because product (even just residue) can ignite explosively. Wear full firefighting turn-out gear (full Bunker gear), and respiratory protection (SCBA).

NFPA Flammable and Combustible Liquids Classification

Combustible Liquid Class II

ROOF KIT WATER STOP
165010

6. ACCIDENTAL RELEASE MEASURES

Personal precautions

For personal protection see section 8. Eliminate all ignition sources (flares, flames including pilot lights, electrical sparks). Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed. Stop spill at source. Prevent from entering drains, sewers, streams or other bodies of water. Prevent from spreading. If runoff occurs, notify authorities as required. Pump or vacuum transfer spilled product to clean containers for recovery. Absorb unrecoverable product. Transfer contaminated absorbent, soil and other materials to containers for disposal. Eliminate all sources of ignition such as flares, flames (including pilot lights), and electrical sparks.

Environmental precautions

No data

Methods for cleaning up

Absorb liquid on vermiculite, floor absorbent, or other absorbent material and transfer to hood.

7. HANDLING AND STORAGE

Handling

Containers of this material may be hazardous when emptied. Since emptied containers retain product residues (vapor, liquid, and/or solid), all hazard precautions given in the data sheet must be observed. Static ignition hazard can result from handling and use. Electrically bond and ground all containers, personnel and equipment before transfer or use of material. Special precautions may be necessary to dissipate static electricity for non-conductive containers. Use proper bonding and grounding during product transfer as described in National Fire Protection Association document NFPA 77.

Storage

Store in a cool, dry, ventilated area, away from incompatible substances.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Guidelines

MINERAL SPIRITS REGULAR		8052-41-3
ACGIH	time weighted average	100 ppm
NIOSH	Recommended exposure limit (REL):	350 mg/m3

ASHLAND
SAFETY DATA SHEET

Page: 6
Revision Date: 01/20/2010
Print Date: 1/22/2010
MSDS Number: R0205917
Version: 1.11

ROOF KIT WATER STOP
165010

NIOSH	Ceiling Limit Value and Time Period (if specified):	1,800 mg/m3	
OSHA Z1	Permissible exposure limit	500 ppm	
OSHA Z1	Permissible exposure limit	2,900 mg/m3	
OSHA Z1A	time weighted average	100 ppm	
OSHA Z1A	time weighted average	525 mg/m3	
US CA OEL	Time Weighted Average (TWA) Permissible Exposure Limit (PEL):	100 ppm	
US CA OEL	Time Weighted Average (TWA) Permissible Exposure Limit (PEL):	525 mg/m3	
POLYMER		254504001-5234	
ACGIH	time weighted average	10 mg/m3	Inhalable particles.
ACGIH	time weighted average	3 mg/m3	Respirable particles.
OSHA Z1	Permissible exposure limit	5 mg/m3	Respirable fraction.
OSHA Z1	Permissible exposure limit	15 mg/m3	Total dust.
OSHA Z1A	time weighted average	5 mg/m3	Respirable fraction.
OSHA Z1A	time weighted average	15 mg/m3	Total dust.
US CA OEL	Time Weighted Average (TWA) Permissible Exposure Limit (PEL):	5 mg/m3	Respirable fraction.
US CA OEL	Time Weighted Average (TWA) Permissible Exposure Limit (PEL):	10 mg/m3	Total dust.
US CA OEL	Time Weighted Average (TWA) Permissible Exposure Limit (PEL):	5 mg/m3	Respirable fraction.
US CA OEL	Time Weighted Average (TWA) Permissible Exposure Limit (PEL):	10 mg/m3	Total dust.
US CA OEL	Time Weighted Average (TWA) Permissible Exposure Limit (PEL):	5 mg/m3	Respirable fraction.
US CA OEL	Time Weighted Average (TWA) Permissible Exposure Limit (PEL):	10 mg/m3	Total dust.
CALCIUM CARBONATE		471-34-1	
US CA OEL	Time Weighted Average (TWA) Permissible Exposure Limit (PEL):	5 mg/m3	Respirable fraction.
US CA OEL	Time Weighted Average (TWA) Permissible	10 mg/m3	Total dust.

ROOF KIT WATER STOP
165010

Exposure Limit (PEL):			
NIOSH	Recommended exposure limit (REL):	5 mg/m3	Respirable.
NIOSH	Recommended exposure limit (REL):	10 mg/m3	Total
OSHA Z1	Permissible exposure limit	5 mg/m3	Respirable fraction.
OSHA Z1	Permissible exposure limit	15 mg/m3	Total dust.
OSHA Z1A	time weighted average	5 mg/m3	Respirable fraction.
OSHA Z1A	time weighted average	15 mg/m3	Total dust.
KAOLIN 1332-58-7			
ACGIH	time weighted average	2 mg/m3	Respirable fraction.
NIOSH	Recommended exposure limit (REL):	5 mg/m3	Respirable.
NIOSH	Recommended exposure limit (REL):	10 mg/m3	Total
US CA OEL	Time Weighted Average (TWA) Permissible Exposure Limit (PEL):	2 mg/m3	Respirable dust.
OSHA Z1	Permissible exposure limit	5 mg/m3	Respirable fraction.
OSHA Z1	Permissible exposure limit	15 mg/m3	Total dust.
OSHA Z1A	time weighted average	5 mg/m3	Respirable fraction.
OSHA Z1A	time weighted average	10 mg/m3	Total dust.

General advice

These recommendations provide general guidance for handling this product. Personal protective equipment should be selected for individual applications and should consider factors which affect exposure potential, such as handling practices, chemical concentrations and ventilation. It is ultimately the responsibility of the employer to follow regulatory guidelines established by local authorities.

Exposure controls

Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

Eye protection

Wear chemical splash goggles when there is the potential for exposure of the eyes to liquid, vapor or mist.

Skin and body protection

Wear normal work clothing including long pants, long-sleeved shirts and foot covering to prevent direct contact of the product with the skin. Launder clothing before reuse. If skin irritation

ROOF KIT WATER STOP
165010

develops, contact your facility health and safety professional or your local safety equipment supplier to determine the proper personal protective equipment for your use.

Wear as appropriate:

Safety shoes

Flame-resistant clothing

Wear resistant gloves such as:

Nitrile rubber

Respiratory protection

A NIOSH-approved air-purifying respirator with an appropriate cartridge and/or filter may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits (if applicable) or if overexposure has otherwise been determined. Protection provided by air-purifying respirators is limited. Use a positive pressure, air-supplied respirator if there is any potential for uncontrolled release, exposure levels are not known or any other circumstances where an air-purifying respirator may not provide adequate protection.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state	liquid
Form	No data
Colour	grey
Odour	No data
Boiling point/boiling range	347.50 °C
pH	No data
Flash point	40.00 °C Tag closed cup
Evaporation rate	9.2
Lower explosion limit/Upper explosion limit	0.5 %(V) / 6 %(V)
Vapour pressure	45.000 mmHg @ 78.00 °F
Vapour density	5 (AIR=1)
Density	1.25 g/cm ³ @ 77.00 °F / 25.00 °C 10.4125 lb/gal @ 77.00 °F / 25.00 °C
Solubility	soluble in water
Partition coefficient: n-octanol/water	No data
log Pow	no data available
Autoignition temperature	No data

10. STABILITY AND REACTIVITY

ASHLAND

SAFETY DATA SHEET

Page: 9
Revision Date: 01/20/2010
Print Date: 1/22/2010
MSDS Number: R0205917
Version: 1.11

ROOF KIT WATER STOP
165010

Stability

Stable.

Conditions to avoid

Heat, flames and sparks.

Incompatible products

aluminum salts, strong mineral acids, alkalis, Strong acids, Strong oxidizing agents

Hazardous decomposition products

Aldehydes, carbon dioxide and carbon monoxide, various hydrocarbons

Hazardous reactions

Product will not undergo hazardous polymerization.

Thermal decomposition

No data

11. TOXICOLOGICAL INFORMATION

Acute oral toxicity

MINERAL SPIRITS REGULAR	: LD 50 Rat: > 5 g/kg
POLYMER	: no data available
RESIDUAL OILS (PETROLEUM), SOLVENT-DEWAXED	: no data available
CALCIUM CARBONATE	: LD 50 Rat: 6,450 mg/kg
QUATERNARY AMMONIUM	: LD 50 Rat: > 8 g/kg
MONTMORILLONITE	
KAOLIN	: LD 50 Rat: > 5,000 mg/kg

Acute inhalation toxicity

MINERAL SPIRITS REGULAR	: no data available
POLYMER	: no data available
RESIDUAL OILS (PETROLEUM), SOLVENT-DEWAXED	: no data available
CALCIUM CARBONATE	: no data available
QUATERNARY AMMONIUM	: no data available
MONTMORILLONITE	
KAOLIN	: no data available

Acute dermal toxicity

MINERAL SPIRITS REGULAR	: LD 50 Rabbit: (>) 3 g/kg
-------------------------	----------------------------

ROOF KIT WATER STOP
165010

POLYMER : no data available
RESIDUAL OILS (PETROLEUM), SOLVENT-
DEWAXED : no data available
CALCIUM CARBONATE : no data available
QUATERNARY AMMONIUM : no data available
MONTMORILLONITE : no data available
KAOLIN : LD 50 Rat: > 5,000 mg/kg

12. ECOLOGICAL INFORMATION

Biodegradability

MINERAL SPIRITS REGULAR : no data available
POLYMER : no data available
RESIDUAL OILS (PETROLEUM), SOLVENT-
DEWAXED : no data available
CALCIUM CARBONATE : no data available
QUATERNARY AMMONIUM : no data available
MONTMORILLONITE : no data available
KAOLIN : no data available

Bioaccumulation

MINERAL SPIRITS REGULAR : no data available
POLYMER : no data available
RESIDUAL OILS (PETROLEUM), SOLVENT-
DEWAXED : no data available
CALCIUM CARBONATE : no data available
QUATERNARY AMMONIUM : no data available
MONTMORILLONITE : no data available
KAOLIN : no data available

Ecotoxicity effects

Toxicity to fish

MINERAL SPIRITS REGULAR : no data available
POLYMER : no data available
RESIDUAL OILS (PETROLEUM), SOLVENT-
DEWAXED : no data available
CALCIUM CARBONATE : 96 h LC 50 Gambusia affinis (Mosquito fish): >
56,000.00 mg/l
Method: Static
Mortality
QUATERNARY AMMONIUM : no data available
MONTMORILLONITE : no data available
KAOLIN : no data available

ASHLAND

SAFETY DATA SHEET

Page: 11
Revision Date: 01/20/2010
Print Date: 1/22/2010
MSDS Number: R0205917
Version: 1.11

ROOF KIT WATER STOP
165010

Toxicity to daphnia and other aquatic invertebrates.

MINERAL SPIRITS REGULAR : no data available
POLYMER : no data available
RESIDUAL OILS (PETROLEUM), SOLVENT-
DEWAXED : no data available
CALCIUM CARBONATE : no data available
QUATERNARY AMMONIUM : no data available
MONTMORILLONITE
KAOLIN : no data available

Toxicity to algae

MINERAL SPIRITS REGULAR : no data available
POLYMER : no data available
RESIDUAL OILS (PETROLEUM), SOLVENT-
DEWAXED : no data available
CALCIUM CARBONATE : no data available
QUATERNARY AMMONIUM : no data available
MONTMORILLONITE
KAOLIN : no data available

Toxicity to bacteria

MINERAL SPIRITS REGULAR : no data available
POLYMER : no data available
RESIDUAL OILS (PETROLEUM), SOLVENT-
DEWAXED : no data available
CALCIUM CARBONATE : no data available
QUATERNARY AMMONIUM : no data available
MONTMORILLONITE
KAOLIN : no data available

Biochemical Oxygen Demand (BOD)

MINERAL SPIRITS REGULAR : no data available
POLYMER : no data available
RESIDUAL OILS (PETROLEUM), SOLVENT-
DEWAXED : no data available
CALCIUM CARBONATE : no data available
QUATERNARY AMMONIUM : no data available
MONTMORILLONITE
KAOLIN : no data available

Chemical Oxygen Demand (COD)

MINERAL SPIRITS REGULAR : no data available
POLYMER : no data available
RESIDUAL OILS (PETROLEUM), SOLVENT- : no data available

ROOF KIT WATER STOP
165010

DEWAXED
CALCIUM CARBONATE : no data available
QUATERNARY AMMONIUM : no data available
MONTMORILLONITE
KAOLIN : no data available

Additional ecological information

MINERAL SPIRITS REGULAR : no data available
POLYMER : no data available
RESIDUAL OILS (PETROLEUM), SOLVENT-
DEWAXED : no data available
CALCIUM CARBONATE : no data available
QUATERNARY AMMONIUM : no data available
MONTMORILLONITE
KAOLIN : no data available

13. DISPOSAL CONSIDERATIONS

Waste disposal methods

Destroy by liquid incineration in accordance with applicable regulations. For assistance with your waste management needs - including disposal, recycling and waste stream reduction, contact Ashland Distribution's Environmental Services Group at 800-637-7922.

14. TRANSPORT INFORMATION

REGULATION

ID NUMBER	PROPER SHIPPING NAME	*HAZARD CLASS	SUBSIDIARY HAZARDS	PACKING GROUP	MARINE POLLUTANT /LTD. QTY.
-----------	----------------------	---------------	--------------------	---------------	-----------------------------

MEXICAN REGULATION FOR THE LAND TRANSPORT OF HAZARDOUS MATERIALS AND WASTES

UN 1133	ADHESIVOS	3		III	
---------	-----------	---	--	-----	--

INTERNATIONAL AIR TRANSPORT ASSOCIATION - PASSENGER

UN 1133	Adhesives	3		III	
---------	-----------	---	--	-----	--

INTERNATIONAL AIR TRANSPORT ASSOCIATION - CARGO

UN 1133	Adhesives	3		III	
---------	-----------	---	--	-----	--

INTERNATIONAL MARITIME DANGEROUS GOODS

ASHLAND
SAFETY DATA SHEET

Page: 13
Revision Date: 01/20/2010
Print Date: 1/22/2010
MSDS Number: R0205917
Version: 1.11

ROOF KIT WATER STOP
165010

UN	1133	ADHESIVES	3	III	LIMITED QUANTITY
----	------	-----------	---	-----	---------------------

TRANSPORT CANADA - INLAND WATERWAYS

UN	1133	ADHESIVES	3	III	LIMITED QUANTITY
----	------	-----------	---	-----	---------------------

TRANSPORT CANADA - RAIL

UN	1133	ADHESIVES	3	III	LIMITED QUANTITY
----	------	-----------	---	-----	---------------------

TRANSPORT CANADA - ROAD

UN	1133	ADHESIVES	3	III	LIMITED QUANTITY
----	------	-----------	---	-----	---------------------

U.S. DOT - INLAND WATERWAYS

UN	1133	Adhesives	3	III	LIMITED QUANTITY
----	------	-----------	---	-----	---------------------

U.S. DOT - RAIL

UN	1133	Adhesives	3	III	LIMITED QUANTITY
----	------	-----------	---	-----	---------------------

U.S. DOT - ROAD

UN	1133	Adhesives	3	III	LIMITED QUANTITY
----	------	-----------	---	-----	---------------------

*ORM = ORM-D, CBL = COMBUSTIBLE LIQUID

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

15. REGULATORY INFORMATION

California Prop. 65

This product does not contain any chemicals known to the State of California to cause cancer, birth, or any other reproductive defects.

ASHLAND
SAFETY DATA SHEET

Page: 14
Revision Date: 01/20/2010
Print Date: 1/22/2010
MSDS Number: R0205917
Version: 1.11

ROOF KIT WATER STOP
165010

SARA Hazard Classification

Fire Hazard
Acute Health Hazard

New Jersey RTK Label Information

POLYMER (S)	
MINERAL SPIRITS REGULAR	8052-41-3
POLYMER	254504001-5234
RESIDUAL OILS (PETROLEUM), SOLVENT-DEWAXED	64742-62-7
POLYMER	800986-5092P
CALCIUM CARBONATE	471-34-1
QUATERNARY AMMONIUM MONTMORILLONITE	68953-58-2

Pennsylvania RTK Label Information

POLYMER (S)	
MINERAL SPIRITS REGULAR	8052-41-3
POLYMER	254504001-5234
RESIDUAL OILS (PETROLEUM), SOLVENT-DEWAXED	64742-62-7
POLYMER	800986-5092P
CALCIUM CARBONATE	471-34-1
QUATERNARY AMMONIUM MONTMORILLONITE	68953-58-2
KAOLIN	1332-58-7

Notification status

EU. EINECS	y (positive listing)
US. Toxic Substances Control Act	y (positive listing)
Australia. Industrial Chemical (Notification and Assessment) Act	y (positive listing)
Canada. Canadian Environmental Protection Act (CEPA).	y (positive listing)
Domestic Substances List (DSL). (Can. Gaz. Part II, Vol. 133)	
Japan. Kashin-Hou Law List	n (Negative listing)
Korea. Toxic Chemical Control Law (TCCL) List	n (Negative listing)
Philippines. The Toxic Substances and Hazardous and Nuclear Waste Control Act	y (positive listing)
China. Inventory of Existing Chemical Substances	y (positive listing)
New Zealand. Inventory of Chemicals (NZIoC), as published by ERMA New Zealand	n (Negative listing)

	HMIS	NFPA
Health	1	1
Flammability	2	2

ASHLAND
SAFETY DATA SHEET

Page: 15
Revision Date: 01/20/2010
Print Date: 1/22/2010
MSDS Number: R0205917
Version: 1.11

ROOF KIT WATER STOP
165010

Physical hazards	0	
Instability		0
Specific Hazard	--	--

16. OTHER INFORMATION

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This MSDS has been prepared by Ashland's Environmental Health and Safety Department (1-800-325-3751).